

the Control Freak™ Home

the Control °Freak®



| | | |
|-------------------------------|---|---|
| Temperature Range | 86 °F–482 °F | 86 °F–482 °F |
| Intensity Control | 3x Intensity Control | 3x Intensity Control |
| Sensors & Accuracy | Dual NTC Sensors (+/-1.8 °F) | Dual NTC Sensors (+/-1.8 °F) |
| Probe | Dual NTC Temperature Probe | Dual NTC Temperature Probe |
| Voltage & Wattage | 110–120v, 1800W | 110–120v, 1800W |
| Product Size | 16.9” x 12.2” x 4.1” | 17.3” x 14.5” x 4.3” |
| Interface | Color Touch Screen | Color Screen |
| Construction | 0.4 mm Stainless Steel Polymer Chassis Sealed Ceramic Glass | 0.8 mm Stainless Steel Metal Chassis Bonded Ceramic Glass |
| Cooling System | Dual Fan Cooling | Dual Fan Cooling |
| Certification | UL/IEC Commercial Certification | NSF Commercial Certification |
| Warranty | 2 Year Consumer Limited Product Warranty | 2 Year Commercial Limited Product Warranty |
| Accessories | Accessory Storage Box Probe Pot Clip — — | Accessory Storage Box Probe Pot Clip USB Tough Padded Carry Case |

Precision, power, sensors, and probe are the same between the two models.

The Control Freak Home is smaller, with a large touch screen.

The Control °Freak has a thicker shell, powerful cooling system, and IPX3-rated water protection for a commercial kitchen environment.

The Control °Freak has a USB port and includes a carrying case.