

**the Control Freak™ Home**

**the Control °Freak®**



<b>Temperature Range</b>	86 °F–482 °F	77 °F–482 °F
<b>Intensity Control</b>	3x Intensity Control	3x Intensity Control
<b>Sensors &amp; Accuracy</b>	Dual NTC Sensors (+/-1.8 °F)	Dual NTC Sensors (+/-1.8 °F)
<b>Probe</b>	Dual NTC Temperature Probe	Dual NTC Temperature Probe
<b>Voltage &amp; Wattage</b>	110–120v, 1800W	110–120v, 1800W
<b>Dimensions (WxDxH)</b>	12.2” x 16.9” x 4.1”	14.5” x 17.3” x 4.3”
<b>Interface</b>	Color Touch Screen	Color Screen
<b>Construction</b>	0.4 mm Stainless Steel Polymer Chassis Sealed Ceramic Glass	0.8 mm Stainless Steel Metal Chassis Bonded Ceramic Glass
<b>Cooling System</b>	Dual Fan Cooling	Dual Fan Cooling
<b>Certification</b>	UL Household certification.	NSF/UL Commercial & Household certification.
<b>Warranty</b>	2 Year Consumer Limited Product Warranty	2 Year Commercial Limited Product Warranty
<b>Accessories</b>	Accessory Storage Box Probe Pot Clip — —	Accessory Storage Box Probe Pot Clip USB Tough Padded Carry Case

Precision, power, sensors, and probe are the same between the two models.

The Control Freak Home is smaller, with a large touch screen.

The Control °Freak has a thicker shell, powerful cooling system, and IPX3-rated water protection for a commercial kitchen environment.

The Control °Freak has a USB port and includes a carrying case.