

the Control Freak™ Home

the Control °Freak®



Temperature Range	77 °F–482 °F	77 °F–482 °F
Intensity Control	3x Intensity Control	3x Intensity Control
Sensors & Accuracy	Dual NTC Sensors (+/-1.8 °F)	Dual NTC Sensors (+/-1.8 °F)
Probe	Dual NTC Temperature Probe	Dual NTC Temperature Probe
Voltage & Wattage	110–120v, 1800W	110–120v, 1800W
Dimensions (WxDxH)	12.2” x 16.9” x 4.1”	14.5” x 17.3” x 4.3”
Interface	Color Touch Screen	Color Screen
Construction	0.4 mm Stainless Steel Polymer Chassis Sealed Ceramic Glass	0.8 mm Stainless Steel Metal Chassis Bonded Ceramic Glass
Cooling System	Dual Fan Cooling	Dual Fan Cooling
Certification	UL Household certification.	NSF/UL Commercial & Household certification.
Warranty	2 Year Consumer Limited Product Warranty	2 Year Commercial Limited Product Warranty
Accessories	Accessory Storage Box Probe Pot Clip — —	Accessory Storage Box Probe Pot Clip USB Tough Padded Carry Case

Precision, power, sensors, and probe are the same between the two models.

The Control Freak Home is smaller, with a large touch screen.

The Control °Freak has a thicker shell, powerful cooling system, and IPX3-rated water protection for a commercial kitchen environment.

The Control °Freak has a USB port and includes a carrying case.